



ARTISAN

— ELEMENTS —

EXTERIOR PRODUCTS SPECIFICATIONS

Artisan Element products are made of raw and recycled materials sourced in the USA and are handcrafted at our Springfield, Missouri production facility. As with all handmade cast products, some degree of color variation is expected. Our casting mediums contain over 50% recycled paper pulp and may qualify for LEED points.

EXTERIOR PRODUCTS: RECOMMENDED

APPLICATIONS

- Planters
- Fire Pits
- Landscape Edging and Curbing

COLOR AND SIZE INFORMATION

- Our standard colors use all natural oxides and pigments and are 100% lead-free
- Due to the handcrafted nature of our product and sources of some quarried ingredients, color variation will occur.
- Standard finish is natural.

PHYSICAL TESTING PROPERTIES

- Class A, Flame Spread Index: 0; Smoke Development Index: 0 (Meets ASTM AE 84 and ANSI/ UL723 standards)
- Sound Transmission (ASTM E 90-09) STC 38
- Density (ASTM C 567) 49.2 lbs per cubic foot
- Flexural Strength (ASTM C 78) 240 psi
- Compressive Strength (ASTM C 39)
 - 320 psi – 28-day cycle
 - 560 psi – 56-day cycle

MANUFACTURING INFORMATION

- All of our products are manufactured by our experienced casting team in Springfield, Missouri.
- Our materials are locally sourced.
- The medium is environmentally friendly with no waste by-products throughout the manufacturing process.
- We recycle our water back into the subsequent casting.

LEAD TIMES

- Our product has similarities to concrete; therefore the cast/cure/dry time can be from 14–28 days.
- Standard lead times are 4–6 weeks based on product and quantity. Please contact us for current lead times.

CUSTOM OPTIONS

- Custom design options are available. Color, size, and shape can be modified depending on the project. For more information, contact us with your specific project details.

INSTALLATION

- Please visit artisan-elements.com for detailed instructions. For homeowners, we recommend hiring an experienced professional for best results.
- The product can be cut and worked with standard wood tools (no diamond saw blades or heavy-duty equipment required)

CONSIDERATIONS

- Our product can be successfully sealed, painted, stained or acid-stained with exterior surfactants.
- Due to the semi-porous nature of the product, do not use harsh chemicals, abrasives or pressure wash. These may cause discoloration or deterioration of the product.
- Fire Pit: do not use lighting fluid directly on the fire pit surface (we recommend using Artisan Element's Fire Logs or fire stick starters)

Published: August 2018